



QUALITY WITHOUT
COMPROMISE



FOOD PACKAGING

| VACUUM PACKAGING CHAMBERS

DESIGN, INNOVATION AND QUALITY

FOOD PACKAGING

PAGE 3

VACUUM TABLE TOP
250 | 350 | 350D | 380 | 380T

PAGE 7

VACUUM SINGLE CHAMBER
450A | 450T | 550A | 560A | 580A

PAGE 10

VACUUM DOUBLE CHAMBER
420A | 600A | 620A | 650A

FOOD PACKAGING

Sipromac vacuum packaging solutions ensure freshness and prolonged shelf life of your food products.



VACUUM
SINGLE
CHAMBER

VACUUM SINGLE CHAMBER

Models | 450A | 450T | 550A | 560A | 580A

HEAVY-DUTY

This high-quality, user-friendly, and easy to clean machine integrates heavy-duty parts, thereby providing great reliability.

PERFORMANCE

This model is designed to package large volumes of oversized products. The modified atmosphere packaging (MAP) option increases the product's shelf life, provides extra protection, prevents colouring.

CERTIFIED

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to UL STD. They are designed for easy cleaning and comply with the industry's highest hygiene and food safety standards.

WHY SHOULD YOU VACUUM PACK ?

- 1 To reduce spoilage by removing air from the package resulting in much longer shelf life;
- 2 To prevent dehydration;
- 3 For ease of handling;
- 4 To slow down oxidation;
- 5 To protect against external contamination.



MODÈLE 450T

SEAL BARS	Length	A	19.1" (485 mm)
	Qty		2
	Distance between	B	22" (559 mm)
CHAMBER DIMENSIONS	Height		8" (203 mm)
BUSCH PUMP	Std.		20 m ³ /h
	Width	E	30.5" (775 mm)
	Depth	F	28" (711 mm)
MACHINE DIMENSIONS	Height	G	21" (533 mm)
	POWER SUPPLY		120 V / 1 pH / 60 Hz
MICROPROCESSOR			MC-40

VACUUM SINGLE CHAMBER


Models | 450A | 450T | 550A | 560A | 580A




MODELS 450A, 550A, 560A AND 580A

		450A	550A	560A	580A
SEAL BARS	Length	A 19.1" (485 mm)	26" (660 mm)	26" (660 mm)	33.5" (855 mm)
	Qty	2	2	2	2
	Distance between	B 23" (584 mm)	23.25" (591 mm)	31" (787 mm)	36.75" (933 mm)
CHAMBER DIMENSIONS	Height	9.5" (241 mm)	8" (203 mm)	8" (203 mm)	8" (203 mm)
BUSCH PUMP	Std.	40 m ³ /h	63 m ³ /h	100 m ³ /h	200 m ³ /h
	Width	E 30.5" (775 mm)	31" (787 mm)	38" (965 mm)	45.25" (1,153 mm)
MACHINE DIMENSIONS	Depth	F 32" (813 mm)	36" (914 mm)	36" (914 mm)	46.5" (1,183 mm)
	Height	G 44" (1,118 mm)	47" (1,194 mm)	47" (1,194 mm)	43.75" (1,113 mm)
	POWER SUPPLY	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40	MC-40	MC-40

2 SEAL BARS



MC-40



BASIC FEATURES

- Single chamber
- Stainless steel construction
- Twin seal element – Double seam band
- Vacuum sensor - Vacuum level controlled in percentage, directly with Microprocessor
- Filler plates
- Cover latch
- Wheels (stainless steel)
- Rear panel
- Crate
- Certification: ETL listed C & US (CSA & UL)

OPTIONAL FEATURES

- Electric cut-off - Two wire seal system: outside wire cuts off excessive part of bag
- Bi-active seal - Sealing from top and bottom for thick pouches and aluminum bags on models 550A, 560A and 580A
- Modified atmosphere packaging (MAP) - Increases the product's shelf life, provides extra protection, prevents colouring
- Air regulator – Regulates air pressure in the seal bars bladders with compressed air (not included)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- 12" (305 mm) chamber lid on models 550A, 560A and 580A
- Vacuum pump sizes
- Stainless steel tilted insert for liquid products
- Silencer
- Other voltages available
- Heated control box for microprocessor
- Service kit for standard maintenance

All features are subject to change without notice.

QUALITY WITHOUT COMPROMISE

SIPROMAC.COM



FOOD PACKAGING

- VACUUM TABLE TOP
- VACUUM SINGLE CHAMBER
- VACUUM DOUBLE CHAMBER

Your authorized retailer:



QUEBEC, CANADA 🇨🇦
2555 Alfred Nobel, Drummondville, QC Canada, J2A 0L5
P : 819 395.5151 1 855 395.5252 F : 819 395.5343
www.sipromac.com