



CRYOGENIC CABINETS

MODEL

- BF-40

BASIC FEATURES

- Stainless-steel fabrication – door, floor, ceiling, inside & outside walls, piping, ventilation, nozzles, etc.
- 8 ¼ stainless steel tube exhaust stack
- Welded assembly in factory
- 4" (101,6 mm) insulation (including the door) of urethane foam
- 1 smoke truck (stainless-steel) with screens or trays
- Internal axial ventilation system with 6 Motors 0.5 HP (3.0 HP total) dual flow
- Temperature controller with chamber temperature and internal product temperature probe (core)
- LIN independent injection valve solenoid and CGA 255 cryogenic transfer hose connector
- Manufactured according to B51/ASME B31.3 CSA, CGA with approved components (RCN)
- The unit and its components are designed for easy cleaning (water resistant) and comply with standards of hygiene and food industry sanitation standard
- CSA Certification

MODEL BF-40

DIMENSIONS INCLUDING CONTROL BOX	Length A	58.5" (1,477 mm)
	Depth B	54.5" (1,385 mm)
	Height C	79.9" (2,028 mm)
INTERNAL DIMENSIONS	Length A	39.0" (990 mm)
	Depth B	45.3" (1,150 mm)
	Height C	70.9" (1,800 mm)
CAPACITY IN LBS.	700 lbs. / 317 kg (Bone-in ham)	
NUMBER OF TROLLEYS / CAPACITY IN LBS.	1 x 12 levels	
VENTILATION (HP) MOTOR (KWH)	3 x 0.5 Hp / Total 1.5 Hp	
POWER SUPPLY	208-220 V / 3 pH / 60 Hz	
MICROPROCESSOR	Touch Screen	

OPTIONAL FEATURES

- Automatic dual temperature recorder
 - Additional trucks
 - Stainless steel screens
 - Stainless steel trays
 - Other voltages available
 - Service kit for standard maintenance
- All features are subject to change without notice.*



MACHINE DIMENSIONS

