



SMOKEHOUSES, COOKING/DRYING UNITS, STEAM COOKING HOUSES

MODELS

- SC-20 • SC-40 • S-11
- S-12 • S-13

BASIC FEATURES

- Stainless-steel fabrication – door, floor, ceiling, inside & outside walls, ventilation etc.
- Welded assembly in factory
- 3" (76 mm) insulation (including the door) of high grade density rock wool
- Triple temperature controls: cabinet, humidity and inside product temperature
- Automatic damper (closing & opening system)
- Variable speed
- Semi-automatic cleaning and rinsing system for cabinet, smoke generator and piping
- Automatic water supply for probe water tank
- End of cycle alarm
- CSA Certification

OPTIONAL FEATURES

- Vertical or Horizontal Air Flow
- Industrial units welded
- Showering system
- Automatic dual temperature recorder (digital - paperless or analog - charts)
- Liquid smoke system (pressure tank, regulator, valves, nozzles)
- Automatic smoke generator (sawdust type)
- Steam generator 6 KW, 12 KW and 18 KW (selected models)
- Cooling system for cold smoking (with compressor)
- Steam heating with stainless steel exchanger coils (selected models)
- Steaming ramp for steam
- Automatic door opener
- Door (extra) for Tunnel Type
- Additional trucks
- Additional levels
- Stainless steel screens
- Stainless steel trays
- Stainless steel sticks: round or triangular
- Other voltages available
- Service kit for standard maintenance

All features are subject to change without notice.

MODEL SC-20

DIMENSIONS INCLUDING CONTROL BOX	Width	A	60" (1,523 mm)
	Depth	B	47.5" (1,089 mm)
	Height	C	95" (2,414 mm)
LOADING CAPACITY (Ham, Bone-in)	450 lbs. (204 Kg)		
NB. OF TROLLEYS	1 x 5 levels		
MAX. TEMPERATURE	322 °F (160 °C)		
VENTILATION / HP MOTOR	3 HP		
POWER SUPPLY	208-220 V / 3 pH / 60 Hz		
MICROPROCESSOR	Touch screen		



SMOKEHOUSES, COOKING/DRYING UNITS, STEAM COOKING HOUSES

MODEL SC-40

DIMENSIONS INCLUDING CONTROL BOX	Width	A	57" (1,444 mm)
	Depth	B	48.75" (1,240 mm)
	Height	C	115" (2,922 mm)
LOADING CAPACITY (Ham, Bone-in)	700 lbs. (317 Kg)		
NB. OF TROLLEYS	1 x 8 levels		
MAX. TEMPERATURE	322 °F (160 °C)		
VENTILATION / HP MOTOR	3 HP		
POWER SUPPLY	208-220 V / 3 pH / 60 Hz		
MICROPROCESSOR	Touch screen		



MODEL S-11, S-12 AND S-13

		S-11	S-12	S-13
DIMENSIONS INCLUDING CONTROL BOX	Width	A 57" (1,444 mm)	57" (1,444 mm)	57" (1,444 mm)
	Depth	B 48.75" (1,240 mm)	48.75" (1,240 mm)	48.75" (1,240 mm)
	Height	C 115" (2,922 mm)	115" (2,922 mm)	115" (2,922 mm)
LOADING CAPACITY (Ham, Bone-in)		1,200 lbs. (544 Kg)	2,400 lbs. (1,089 Kg)	3,600 lbs. (1,633 Kg)
NB. OF TROLLEYS		1 x 8 levels	2 x 8 levels	3 x 8 levels
MAX. TEMPERATURE		322 °F (160 °C)	322 °F (160 °C)	322 °F (160 °C)
VENTILATION / HP MOTOR		5 HP	10 HP	15 HP
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		Touch screen	Touch screen	Touch screen

MACHINE DIMENSIONS

