



# VACUUM TABLE TOP

## MODELS

- 250 • 300 • 300D • 350
- 350D • 380 • 380T

## BASIC FEATURES

- Table top single chamber
- Stainless steel construction
- Clear (see-through) lid
- Twin seal element
- Vacuum sensor - Vacuum level controlled in percentage, directly with Microprocessor (except model 300-300D)
- Filler plates
- Cover latch
- Feet
- Rear panel
- Crate
- Certification: ETL listed C & US (CSA & UL) (except model 300-300D)
- Certification: ETL Sanitation Listed (NSF)

## MODEL 250

<b>SEAL BARS</b>	<b>Length</b>	<b>A</b>	12.5" (319 mm)
	<b>Qty</b>		1
	<b>Distance to back</b>	<b>B</b>	13.1" (333 mm)
	<b>Distance between</b>	<b>C</b>	N/A
<b>CHAMBER DIMENSIONS</b>	<b>Height</b>		4" (102 mm)
<b>BUSCH PUMP</b>	<b>Std.</b>		8m <sup>3</sup> 0.35 Kw
<b>MACHINE DIMENSIONS</b>	<b>Width</b>	<b>E</b>	17" (430 mm)
	<b>Depth</b>	<b>F</b>	20.7" (525 mm)
	<b>Height</b>	<b>G</b>	17.2" (436 mm)
<b>ELECTRICITY</b>			120 V / 1 pH / 60 Hz
<b>MICROPROCESSOR</b>			MC-40

## OPTIONAL FEATURES

- Electric cut-off - Two wire seal system: outside wire cuts off excessive part of bag
- Modified atmosphere packaging (MAP) - Increases the product's shelf life, provides extra protection, prevents colouring (except model 300-300D)
- Air regulator – Regulates air pressure in the seal bars bladders with compressed air (not included) (except model 300-300D)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- Stainless steel tilted insert for liquid products
- Silencer
- Stainless Steel cart
- Other voltages available
- Service kit for standard maintenance

*All features are subject to change without notice.*



# VACUUM TABLE TOP


## MODELS 380 AND 380T

		380	380T
SEAL BARS	Length	A 12.5" (319 mm)	12.5" (319 mm) & 32.2" (817 mm)
	Qty	2	3
	Distance to back	B N/A	12" (306 mm)
	Distance between	C 36.1" (918 mm)	36.1" (918 mm)
CHAMBER DIMENSIONS	Height	6.8" (172 mm)	6.8" (172 mm)
BUSCH PUMP	Std.	20 m <sup>3</sup> 0.9 kW	20 m <sup>3</sup> 0.9 kW
MACHINE DIMENSIONS	Width	E 42.9" (1,090 mm)	42.9" (1,090 mm)
	Depth	F 25.5" (648 mm)	25.5" (648 mm)
	Height	G 19.2" (487 mm)	19.2" (487 mm)
ELECTRICITY		120 V / 1 pH / 60 Hz	120 V / 1 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40




### MACHINE DIMENSIONS


1 SEAL BAR



2 SEAL BARS



3 SEAL BARS




### CONTROL PANELS

MC-05



MC-40



# VACUUM TABLE TOP

## MODELS 300 AND 300D

		300	300D
SEAL BARS	Length	A	19.1" (485 mm)
	Qty		1
	Distance to back	B	15.4" (391 mm)
	Distance between	C	N/A
CHAMBER DIMENSIONS	Height		6.8" (172 mm)
BUSCH PUMP	Std.		20 m <sup>3</sup> 0.9 kW
MACHINE DIMENSIONS	Width	E	23" (585 mm)
	Depth	F	23.7" (602 mm)
	Height	G	19.7" (500 mm)
ELECTRICITY			120 V / 1 pH / 60 Hz
MICROPROCESSOR		MC-05	MC-05



## MODELS 350 AND 350D

		350	350D
SEAL BARS	Length	A	19.1" (485 mm)
	Qty		1
	Distance to back	B	15.4" (391 mm)
	Distance between	C	N/A
CHAMBER DIMENSIONS	Height		6.8" (172 mm)
BUSCH PUMP	Std.		20 m <sup>3</sup> 0.9 kW
MACHINE DIMENSIONS	Width	E	23" (585 mm)
	Depth	F	23.7" (602 mm)
	Height	G	19.7" (500 mm)
ELECTRICITY			120 V / 1 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40

