

VACUUM SINGLE CHAMBER

Models | 450A | 450T | 550A | 560A | 580A

HEAVY-DUTY

This high-quality, user-friendly, and easy to clean machine integrates heavy-duty parts, thereby providing great reliability.

PERFORMANCE

This model is designed to package large volumes of oversized products. The modified atmosphere packaging (MAP) option increases the product's shelf life, provides extra protection, prevents colouring.

CERTIFIED

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to UL STD. They are designed for easy cleaning and comply with the industry's highest hygiene and food safety standards.

WHY SHOULD YOU VACUUM PACK ?

- 1 To reduce spoilage by removing air from the package resulting in much longer shelf life;
- 2 To prevent dehydration;
- 3 For ease of handling;
- 4 To slow down oxidation;
- 5 To protect against external contamination.



MODÈLE 450T

SEAL BARS	Length	A	19.1" (485 mm)
	Qty		2
	Distance between	B	22" (559 mm)
CHAMBER DIMENSIONS	Height		8" (203 mm)
BUSCH PUMP	Std.		20 m ³ 0.9 kW
	Width	E	30.5" (775 mm)
MACHINE DIMENSIONS	Depth	F	28" (711 mm)
	Height	G	21" (533 mm)
POWER SUPPLY			120 V / 1 pH / 60 Hz
MICROPROCESSOR			MC-40

VACUUM SINGLE CHAMBER


Models | 450A | 450T | 550A | 560A | 580A



MODELS 450A, 550A, 560A AND 580A

		450A	550A	560A	580A
SEAL BARS	Length	A 19.1" (485 mm)	26" (660 mm)	26" (660 mm)	33.5" (855 mm)
	Qty	2	2	2	2
	Distance between	B 23" (584 mm)	23.25" (591 mm)	31" (787 mm)	36.75" (933 mm)
CHAMBER DIMENSIONS	Height	9.5" (241 mm)	8" (203 mm)	8" (203 mm)	8" (203 mm)
BUSCH PUMP	Std.	40 m ³ 2.0 HP	63 m ³ 3.0 HP	100 m ³ / 5,0 HP	165 m ³ 7.5 HP
MACHINE DIMENSIONS	Width	E 30.5" (775 mm)	31" (787 mm)	38" (965 mm)	45.25" (1,153 mm)
	Depth	F 32" (813 mm)	36" (914 mm)	36" (914 mm)	46.5" (1,183 mm)
	Height	G 44" (1,118 mm)	47" (1,194 mm)	47" (1,194 mm)	43.75" (1,113 mm)
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40	MC-40	MC-40

2 SEAL BARS



MC-40



BASIC FEATURES

- Single chamber
- Stainless steel construction
- Twin seal element – Double seam band
- Vacuum sensor - Vacuum level controlled in percentage, directly with Microprocessor
- Filler plates
- Cover latch
- Wheels (stainless steel)
- Rear panel
- Crate
- Certification: ETL listed C & US (CSA & UL)

OPTIONAL FEATURES

- Electric cut-off - Two wire seal system: outside wire cuts off excessive part of bag
- Bi-active seal - Sealing from top and bottom for thick pouches and aluminum bags on models 550A, 560A and 580A
- Modified atmosphere packaging (MAP) - Increases the product's shelf life, provides extra protection, prevents colouring
- Air regulator – Regulates air pressure in the seal bars bladders with compressed air (not included)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- 12" (305 mm) chamber lid on models 550A, 560A and 580A
- Vacuum pump sizes
- Stainless steel tilted insert for liquid products
- Silencer
- Other voltages available
- Heated control box for microprocessor
- Service kit for standard maintenance

All features are subject to change without notice.